

# Dual-Lock™



Dual-Lock™

Dual-Lock™ 170 400.

**Dual-Lock 400**

400 (~ 62 / . ).

170

Lock™. 400 ( ) Dual-

**Dual-Lock 250**

250 (~ 39 / . ),

250.

**Dual-Lock 170**

170 Dual-Lock™ 400 ( . ) 170 (~ 26 / . ).

Scotchmate™ Loop™

<p>SJ-3540 250</p> <p>SJ-3541 400</p>	<p>Dual-Lock™</p> <p>50° .</p> <p>“ ”</p>
<p>SJ-3550 250</p> <p>SJ-3560 250</p>	<p>Dual-Lock™ VHB™,</p> <p>( . ) .</p> <p>95°</p> <p>100%</p> <p>30° 70°</p> <p>(SJ-3560)</p> <p>SJ-3560</p> <p>-20° 95° , 0%</p>

( )


# Dual-Lock™



	<b>SJ-3540</b>	SJ-3541	SJ-3560	SJ-3550
( / )	- /	- /	/ VHB	/ VHB
				±0,5
<b>SJ-3540/SJ-3540</b>				4,1
SJ-3550/SJ-3550				5,8
SJ-3560/SJ-3560				5,8
a ( / )				>1000
b				1

b Dual-Lock 12 21° 50%

22,2° 50%	b	
	[ ]	[ ]
250 / 250	103	242-311
250 / 400	309 ( )	311-380

a 170/ 170. 400/ 400

b 305 /

## SJ-3560

<b>SJ-3560</b>		<b>CARC</b> <b>(Chemical agent resistant coating)</b>
	<b>254.5</b>	<b>1026.6</b>

22° 50%		
	/	/
	280	280

a 170/ 170. 400/ 400

b 14 22° 280 / 14 22° 280 /

60<sup>2</sup> 1 ( )

<b>SJ3540, 3541</b>	-30° 50°	-30° 70°	
SJ3550	-30° 70°	-30° 93°	
SJ3560	-30° 70°	-30° 93°	

## SJ3551/3552

,77 155 /<sup>2</sup> 7  
93°  
! 50°

# Dual-Lock™



72- SJ3560. 20° . 48 SJ3541/3542 48  
1359 1357F 3 Scotch-Grip™ 4693, 847,  
! ( )

3